

NCW-11

CONNECTION WIRE

The NCW-11 is a 3-cored wire to be conducted through a wall-mounted extraction arm. The NCW-11 is used to connect a working light or working light + automatic start/stop (arc sensor) which is installed in the hood of the arm, to a control box.




x7

SPECIFICATIONS

■ Physical dimensions and properties	
Length	11 m
Wire diameter	3 x 0,75 mm ²
Sheath colour	grey
Colour codes	white (WH), brown (BN), green (GN) (according to DIN 47100)
Weight (net)	595 g
■ Product combinations	
<ul style="list-style-type: none"> • WL • CB • T-Flex, Flex-2/3/4, UltraFlex-3/4, UltraFlex-4/LC 	<ul style="list-style-type: none"> • working light • control box • extraction arm
<ul style="list-style-type: none"> • WL+AST • CB • T-Flex, Flex-2/3/4, UltraFlex-3/4, UltraFlex-4/LC 	<ul style="list-style-type: none"> • working light + automatic start/stop • control box • extraction arm
■ Scope of supply	
11 m connection wire - tie-wrap (7)	
■ Order information	
Article number	9850031050
Number/package	1
■ Shipping data	
Gross weight	685 g
Packing dimensions	envelope 350 x 250 mm
Harmonized Tariff Code	8421.9900.99
Country of origin	the Netherlands

APPROVALS/CERTIFICATES

	Directive 2011/65/EC (RoHS) valid as of 8 June 2011
---	---

Product type	NCW-11
Article no.	9850031050
Product category	Options and accessories
Version	080212/C

Always check the latest version on www.plymovent.com.